

# **Phasing Sustainability**

low tech sustainable housing prototype

A THESIS  
SUBMITTED TO THE FACULTY OF THE GRADUATE SCHOOL  
OF THE UNIVERSITY OF MINNESOTA  
By

Jeffrey William Ankeny

IN PARTIAL FULFILLMENT OF THE REQUIREMENTS  
FOR THE DEGREE OF  
MASTER OF ARCHITECTURE

Mary Guzowski  
Director of Graduate Studies

February 2012



## Acknowledgments

---

I would like to thank my wife, Maria, and my two sons, Devin and Andrew, for their tremendous amount of patience and support throughout my thesis. I would also like to thank my father, mother, and sister for helping and encouraging me during difficult times.

Also, thanks to the following mentors for their guidance and patience:

William Conway, Thesis Chair

Mary Guzowski, Thesis Committee Member

William Weber, Thesis Committee Member

# Table of Contents

---

Acknowledgments.....	i
Table of Contents.....	ii
List of Figures.....	iii
Hypothesis Statement.....	1
Thesis Statement.....	2
Research Statement.....	3
Research and Scholarship in the Field.....	5
<b>Phasing Sustainability</b>	
Village of Troncones.....	7
Thermal Comfort:	
Short Term Phase.....	8
Mid Term Phase.....	10
Long Term Phase.....	12
Water Management:	
Short Term Phase.....	14
Mid Term Phase.....	16
Long Term Phase.....	18
Conclusion.....	20
Endnotes.....	21
Annotated Bibliography.....	22
Bibliography.....	23
Appendix:	
Thesis Presentation Boards.....	24-27

## List of Figures

---

figure	page	image	source
1.1	1	River in Troncones	by author
1.2	1	Existing House	by author
2.1	2	Phasing Sustainability	by author
3.1	3	Existing Housing Condition	by author
3.2	3	BaSiC Initiative	<a href="http://www.basicinitiative.org">www.basicinitiative.org</a>
4.1	4	Stopplaere House	ArchNet Digital Library:Hassan Fathy Archives, <a href="http://www.archnet.org">www.archnet.org</a>
4.2	4	Making Tiles	Building Materials & Technology Promotion Council
4.3	4	Micro Concrete Roof	Building Materials & Technology Promotion Council
5.1	5	Adobe Bricks	<a href="http://www.basicinitiative.org">www.basicinitiative.org</a>
5.2	5	Stopplaere House	ArchNet Digital Library:Hassan Fathy Archives, <a href="http://www.archnet.org">www.archnet.org</a>
6.1	6	Micro Concrete Tiles (MCR)	MIPROMALO, <a href="http://www.mipromalo.com">www.mipromalo.com</a>
7.1	7	Site Map of Troncones	by author
7.2	7	Map of Mexico	NASA, <a href="http://www.earthobservatory.nasa.gov">www.earthobservatory.nasa.gov</a>
7.3	7	Images of Troncones	by author
8.1	8	Short Term Floor Plan	by author
8.2	8	Windflow Studies	by author
8.3	8	Windflow Studies	by author
8.4	8	Airflow Diagram	by author
8.5	8	Ventilation Calcs	by author
9.1	9	Sun Path Studies	by author
9.2	9	Sun Path Studies	by author
9.3	9	Indigenous Flora	by author
9.4	9	Low Tech Solar Control	by author
10.1	10	Hot Segmented Spaces	by author
10.2	10	Mid Term Floor Plan	by author
10.3	10	Extending Exterior	by author
10.4	10	Longitudinal Section	by author
10.5	10	Exterior Habitation	by author
10.6	10	Windflow Studies	by author
10.7	10	Windflow Studies	by author
11.1	11	Solar Controls	by author
11.2	11	Solar Controls	by author
11.3	11	Solar Controls	by author
11.4	11	Solar Controls	by author
12.1	12	Long Term Floor Plan	by author
12.2	12	Windflow Studies	by author

## List of Figures

---

figure	page	image	source
12.3	12	Sun Path Studies	by author
12.4	12	Exterior Living Spaces	by author
12.5	12	Adobe Brick Data & Diagram	by author
13.1	13	Thermal Mass	by author
13.2	13	East Perspective	by author
13.3	13	Indigenous Roofing Data	by author
14.1	14	Short Term Floor Plan	by author
14.2	14	Water Delivery	by author
14.3	14	Water Usage	by author
14.4	14	Troncones Water Cycle	by C.W. Thornthwaite Associates, Water Balance Data
15.1	15	Rainwater Harvesting Calcs	by author
15.2	15	Rainwater Collection Diagram	by author
15.3	15	East Perspective	by author
15.4	15	Rainwater Collection	by author
15.5	15	Water for Irrigation	by author
16.1	16	Mid Term Floor Plan	by author
16.2	16	East Perspective	by author
16.3	16	Water Management Diagram	by author
17.1	17	Section at Compost Toilet	by author
17.2	17	SouthEast Perspective	by author
17.3	17	Multi-Step Compost Bin	by author
17.4	17	Water Usage	by author
18.1	18	Long Term Floor Plan	by author
18.2	18	Water Pump	by Bamford Industries, <a href="http://www.bamford.com.au/rampump/">www.bamford.com.au/rampump/</a>
18.3	18	Rainwater Harvesting Calcs	by author
18.4	18	Daily Water Usage Statistics	by author
19.1	19	Rainwater Collection Diagram	by author
19.2	19	Rainwater Harvesting	by author
19.3	19	Rainwater Collection	by author

# Hypothesis Statement

Mexico, like many developing countries, is in urgent need of housing solutions that incorporate sustainable technologies. While living in Troncones, Mexico for four months, I observed mismanagement of fresh water resources, under-utilized potential of passive solar energy, and a lack of waste management. There was no attempt to conserve resources or to recycle waste. The waste that is produced is burned in backyards, releasing harmful toxins into the atmosphere and detracting from the natural aesthetics of the community. The people of Troncones, Mexico and other developing countries need to be exposed on sustainable practices that form a partnership with nature, revealing the interconnection of technology with the natural world. Losing sight of this connection desensitizes a community's understanding of nature. Architecture and society in general needs to be based on the eco-centric belief that we must be accountable for the well being of all the Earth's inhabitants.



1.1 River in Troncones  
mismanagement of fresh water resources




1.2 Existing House  
hot and segmented living spaces

# Thesis Statement

“It is time to stop designing in the image of the machine and start designing in a way that honors the complexity and diversity of life itself.” -- Stuart Cowan

This thesis proposes a low tech<sup>1</sup> sustainable housing prototype for communities similar to Troncones. The prototype begins with an existing housing condition and reaches a sustainable (ecological) housing condition<sup>2</sup> through phasing. The main goal is to design a successful, repeatable and ecologically sustainable housing prototype that will focus on producing thermal and water technology similar to those produced by the University of Texas design/build program, BaSiC Initiative<sup>3</sup>. The housing prototype is intended to help train local inhabitants in cooperative construction techniques that express the interconnected cycles of technology with nature.



## 2.1 Phasing Sustainability phasing from an existing condition

## Research Statement

---

An existing dwelling in Troncones was chosen to apply the proposed prototype. The dwelling has neglected some of the existing design vernacular of some of the older dwellings. Indigenous adobe brick has been replaced by fired clay brick. The dwelling does not seem to take advantage of the opportunity for passive cooling and has poor infrastructure for water and waste. Existing knowledge gathered on Design-build case studies that focused on low-tech sustainable housing solutions helped to inform this Thesis. Material use and construction methods were examined that could be applied in Troncones and applied to a wider application of similar conditions in various developing countries.

The first precedent that was reviewed, BaSiC Initiative, explores the use of indigenous materials while teaching Design-build methods to architecture students and local inhabitants. Sergio Palleroni, Co-founder and Director of BaSiC Initiative, started the program in 1986 as a program to assist poor indigenous farmers in central Mexico. The BaSiC Initiative program has several case studies which were done in Mexico, using a concrete post and beam structure with adobe brick infill. Similar methods and materials will be used in Troncones.



**3.1 Existing Housing Condition.**

This dwelling in Troncones was chosen to apply the proposed prototype.



**3.2 BaSiC Initiative**

Post and beam housing prototype that is repeatable and sustainable.

The second precedent, the architecture of Hassan Fathy,<sup>4</sup> explores the use of appropriate technology to provide passive cooling solutions. Fathy's use of adobe brick to create thermal mass, ventilation strategies, and his methods for training local inhabitants are low tech sustainable solutions which will be applied in Troncones.

The third precedent, Practical Action<sup>5</sup>, examines the use of new technologies and local resources in order to develop a housing prototype. The prototype is refined and improved by working with indigenous people who are familiar with locally sourced materials. Troncones has similar conditions to the case studies that were researched. The proposed prototype will use local indigenous materials to make adobe bricks and Micro Concrete Roofing tiles (MCR).



**4.1 Hassan Fathy: Stopplaere House**  
Fathy incorporated dense brick walls and traditional courtyard forms to provide passive cooling.



**4.2 - 4.3 Micro Concrete Roofing Tiles**  
Practical Action's goal is to help the local inhabitants use new technologies and bring sustainable improvements to people's lives.

# Research and Scholarship in the Field

Three architectural precedents were examined so that existing design research could be used to inform this thesis by providing examples of issues explored, methods used, and the results of those methods. Useful knowledge gained from the review of these precedents was used to create a thesis that extends existing knowledge of low tech sustainable housing. The use of indigenous materials, passive cooling, and water management are further explored through a series of phased solutions.

In the first precedent, BaSiC Initiative, used a concrete post and beam system to provide structural rigidity. This is typical practice in Mexico, although indigenous adobe brick is used instead of fired clay brick. Some local builders of Troncones know how to make adobe bricks, but it is not practiced because of the availability of fired clay bricks. This thesis reintroduced the use of adobe brick as a primary building material. Adobe bricks can be produced on site because of ideal soil composition and is a cost effective method because labor is so affordable.

The second precedent, the architecture of Hassan Fathy, used extruded window openings, vents just above the floor, exhaust vents in high vaulted areas, and the traditional courtyard to improve air flow. All of these methods were used in this thesis as a passive cooling method to improve thermal comfort.




## 5.1 Local Indigenous Materials

BaSiC Initiative teaches the local inhabitants and students how to use locally available and sustainable building materials.

Earth, straw, and water are used to make sun-dried adobe bricks.

## 5.2 Hassan Fathy - Stopplaere House

Window placement provides good cross-ventilation.



## 5.3 Hassan Fathy - Shahira Mehrez Apartment

Hot air exhaust is located in high vaulted areas.

The third precedent, Practical Action, used Micro Concrete Roofing tiles (MCR) a new technology which is easy to make, with local resources, is half the weight but just as strong as fired clay roofing tile. MCR's are recommended for use in roof repair, ridge venting, and roof addition applications in this thesis.

It is important for the local indigenous people to participate in low-tech and low-cost sustainable building methods through a series of phased strategies. People need to be involved in the building process because they can help advise on the architectural condition and function of spaces, as well as help provide the experience of traditional design vernacular while creating a sustainable housing condition. An existing house is phased towards a sustainable condition, starting with short term conditions which are the easiest to change and lowest cost. The house is then phased to mid term conditions which are larger scale low-tech solutions that are more expensive and labor intensive. Finally, the house will be phased to long term conditions that are the most expensive and labor intensive of all sustainable solutions.



**6.1 Micro Concrete Tiles (MCR)**  
Roofing alternative that reduces cost and uses local resources.

# Phasing Sustainability: The Village of Troncones

The Village of Troncones is located in the state of Guerrero, Mexico on the Pacific coast. Nine hundred and twenty permanent residents live in this beach community, which caters to vacationers in beach-front rental properties and vacation homes. A majority of the residents live within the impoverished inner-city in small single family homes. Troncones has no infrastructure for water or sewer so septic systems and water storage tanks are used. The village is very hot and humid with a dew point averaging above 70°F. Lack of water management and poor dwelling design relating to thermal comfort have inspired this thesis. The existing house that was chosen to phase sustainability is centrally located within the village.



7.1-7.3 Images of Troncones  
Troncones, Guerrero, Mexico  
Latitude: 17 39'N, Longitude: 101 33'W



# Thermal Comfort - Short Term Phase

Examining the existing thermal comfort issues of the house reveals insufficient ventilation and solar control. The house has few openings on the west side of the house where prevailing winds could help to cool interior spaces. There is no flora or trees close to the house to provide shading.

Windflow studies<sup>6</sup> on the existing conditions with the proposed added openings show a vast improvement in airflow through the interior spaces. The amount of inlet area for proper ventilation was calculated. Venting and windows were added to bring cool air into the house and ridge venting was installed at the roof for hot air to escape.

calculated sizing required for venting  
 total opaque wall area x U<sub>wall</sub> x outside design temp / total floor area  
 $1157 \times .41 \times 15 / 690 = 10.3 \text{ Btu/h sf}$   
 total roof area x U<sub>wall</sub> x outside design temp / total floor area  
 $740 \times .72 \times 35 / 690 = 27 \text{ Btu/h sf}$   
 total = 37.3 Btu/h sf


2.5% (29 sf) of wall area needs to be inlet for ventilation

proposal: adding cross-ventilation  
 add 3'-0" x 4'-0" open celled block windows (2) = 12 sf of venting  
 add 3'-0" x 6" low inlet vents (2) = 3 sf of venting  
 add 3'-0" x 1'-4" venting (3) at east wall  
 15 sf + existing 14 sf = 29 sf for venting


8.5 Ventilation Calcs  
 venting existing house

## Results


**cross-ventilation:**  
 increased ventilation surface area by 200%, 37.3 Btu/h sf



8.1 Short Term Floor Plan  
 Prevailing winds range on average from 265° west to 230° southwest



8.4 Airflow Diagram  
 Cool air enters low, hot air exits at ridge vent



existing condition proposed openings


8.2-8.3 Windflow Studies  
 Prevailing winds from 265° west

Using indigenous flora as a low tech solution for solar control was the short term proposal. Sun path studies<sup>7</sup> were performed during the intense heating period of 10:00 am-4:00 pm on winter and summer solstice to reveal the extreme conditions the sun had on the house. Studies of the existing and proposed conditions provided the necessary information to determine flora placement. The indigenous flora is a low cost solution that will provide shaded exterior spaces for habitation and cooler building surfaces.

**Results**


**flora for shading:**

304 sf of native flora added, providing exterior cooling pockets and shaded building surfaces



9.1-9.2 Sun Path Studies  
Summer solstice during intense heating period

indigenous flora: Camellia  
grows to 8'-10' high  
provides shade  
slows down water flows (runoff)  
and allows the rain to soak into  
the ground



9.3 Indigenous Flora  
Camellia: Grows to 10' high



9.4 Low Tech Solar Control  
Cooler spaces for habitation

# Thermal Comfort - Mid Term Phase

Mid term thermal comfort conditions focus on phasing wall removal and solar controls to the house. The existing house has hot segmented spaces with poor natural lighting.




**10.1 Hot Segmented Spaces**  
View from the existing kitchen/dining into the living room.

Windflow studies show a vast improvement in airflow through the interior spaces by removing walls. Opening the exterior south wall and the interior wall between the living space and the kitchen allows the southwest winds to flow deep into the dwelling.



**10.3 Extending Interior**  
View from living room into the kitchen/dining.

The integrity of the structural concrete post and beam frame is left intact and existing fired clay brick infill is removed to open spaces and extend the interior spaces into exterior areas of habitation. An adobe brick oven was added to provide an exterior cooking space, minimizing interior cooking and helping to provide cooler interior spaces.




**10.2 Mid Term Floor Plan**



**10.4 Longitudinal Section**  
Section at entry porch through the kitchen/dining.



**10.5 Exterior Habitation**  
View through the kitchen/dining into the living room.



mid term phasing winds from 230° southwest




mid term phasing winds from 265° west

**10.6-10.7 Windflow Studies**  
Prevailing winds

The traditional design of vernacular windows in Troncones are open celled concrete blocks within the window opening. The window is open to the sun, wind, and rain providing no solar controls.

Indigenous palm wood and leaves are used to make low tech sliding door and window shutter solar controls. The shutters can provide cooler interior spaces by preventing direct sunlight. The shutters can help provide warmer interior spaces protecting from wind and rain in cooler months.

Sliding shutter is constructed of indigenous palm wood and palm leaves. Sliding shutter slides shut to control sun and wind.



11.1-11.4 Solar Controls  
Sliding window and door shutters

## Results

### wall removal:

280 sf of wall was removed at kitchen to improve interior airflow  
>37.3 Btu/h sf (>30 Btu required)

### sliding shutter:

24 sf at windows  
21 sf at door  
controls airflow/shade

# Thermal Comfort - Long Term Phase

The existing house needed additional space in order to comfortably accommodate a family of four. Long term thermal comfort conditions were introduced in exterior living spaces. Indigenous materials were used for roof and thermal mass walls on the addition to the house.

Exterior living spaces were added to the house to provide cooler spaces of habitation. A dining area and a seated countertop at the kitchen were added areas that provided protection from direct sunlight. Windflow and sun path studies were used to help determine the orientation of the new spaces and window placement to maximize ventilation and shading.



12.4 Exterior Living Spaces  
View at kitchen and dining

Indigenous materials were used to add additional spaces and to repair existing spaces. Troncones has ideal soil composition for making adobe bricks. The bricks were used to make thermal mass walls. Adobe bricks are cheaper than fired clay bricks and can be formed on site.

### Troncones soil composition

Cambisol - sandy loam  
Metamorphics - exposed subsurface rocks by soil erosion

**desirable soils for brick-making:**  
soils classified as loamy sands, sandy loams or sandy clay loams contain sand, clay, and silt ideal for making adobe brick

12.5 Adobe Brick Data and Diagram  
Soil composition and how to make bricks

### procedure

mix



form



cure




4.9 pesos per adobe brick (labor & mat'l)

7.1 pesos per fired clay brick (labor & mat'l)

**31% cost savings**



12.1 Long Term Floor Plan



long term phasing  
265° west →

12.2 Windflow Studies  
Prevailing winds



10 am Jun 21


12.3 Sun Path Studies  
Intense heating period

Micro concrete roofing tiles (MCR) is a local resource that was used in lieu of traditional clay tiles on the house addition and on repairs. The concrete tiles are highly durable, lightweight, and reduce heat gain because they reflect UV rays.

Thermal mass walls were used to increase the thermal lag<sup>8</sup>. The adobe brick wall absorbs the sun's heat during the intense heating period and releases the heat through the roof venting after the night time temperature drops. The wall thickness was increased to 12" to provide a 10 hour thermal lag period for solar heat to pass through the walls.

Use:  
indigenous roof  
(repair and addition)

Micro Concrete  
Roofing tiles (MCR):  
reduced cost  
local resource  
reflects UV rays



Micro Concrete Roofing tiles (MCR)

Roofing	Weight (kg/m <sup>2</sup> )
Clay tiles	40-80
MCR tiles	25-30

13.3 Indigenous Roofing Data  
Micro Concrete Roofing tiles (MCR)

## Results

### exterior living spaces:


exceeds 45 Btu/h sf required for a 2 bedroom dwelling

### indigenous materials:

adobe brick: 31% cost savings  
MCR tiles: lightweight & reflects UV rays

### thermal mass:

.16 U-value = 10 hour thermal lag  
sensible heat gain = 1,906 Btu/h




13.1 Thermal Mass  
Night ventilation of thermal mass



13.2 East Perspective  
Dining and bedroom addition using thermal mass

# Water Management - Short Term Phase


Water availability in Troncones is of major concern. The only time it rains is during the rainy season from June through September. Troncones has no infrastructure for domestic water. Non-potable water is delivered by truck on a weekly basis. Bottled water must also be purchased for potable use. Water costs on average of \$704.00 per person per year.




Troncones residents do not use rainwater as a resource. Rainwater collection was the focus during the short term phase for irrigation use. The water cycle patterns and domestic water usage of Troncones has been reviewed. Civic leader Victor Lopez was interviewed to determine the average daily water usage patterns of Troncones. The water cycle patterns were determined using Global Historical Climatology Network<sup>9</sup> and C.W. Thornthwaite water balance data<sup>10</sup>

## 14.4 Troncones Water Cycle

Water balance data



14.3 Water Usage  
Average person daily usage



14.1 Short Term Floor Plan



14.2 Water Delivery  
Water storage tank being filled


The existing roof was used as the catchment area to collect untreated rainwater for irrigation use. Rainwater harvesting calcs were used to determine the percentage of reduced water usage. A rainwater scupper and downspout system was installed to collect water in a rainwater barrel. A spigot in the barrel allows for water to be collected into multiple barrels or to a hose for irrigation use. The rainwater harvesting calcs revealed that the catchment area will provide enough rainwater to reduce water usage by 25%.

**rainwater harvesting calcs:**

g/cd x population=gpd  
 70.37x4=281.48 gallons per day  
 gpd x 365 days=gal/year  
 281.48x365=102,740.20 gallons per year  
 annual precipitation = 59.35  
 design precipitation = 39.53  
 catchment area (existing)= 1,292 sf  
 roof catchment supplies 25% of total usage  
 25,685 gallons supplied by roof yearly  
 25% total reduced usage

**15.1 Rainwater Calcs**

Existing roof - rain harvesting



**15.5 Water for Irrigation**

Harvested rainwater is used for irrigation


**Results**

**rainwater collection:**


25% total reduced usage  
 53% of irrigation supplied by untreated rainwater

**untreated rainwater for irrigation:**

catchment area (existing)= 1,292 sf  
 roof catchment supplies 25% of total usage  
 53% of irrigation supplied by untreated rainwater



**15.4 Rainwater Collection**  
 Rain harvesting barrel



**15.2 Rainwater Collection Diagram**  
 Short term phase - rain harvesting




**15.3 East Perspective**  
 Short term phase - rain harvesting


# Water Management - Mid Term Phase

The average person in Troncones is paying over 11% of their income for water. Mid term phasing will focus on reducing water usage by using harvested rainwater and a waterless toilet.

A low tech rainwater cistern was used to provide treated water that could be used for domestic purposes but is not intended for potable use. Bottled drinking water needs to be purchased. The cistern was constructed of adobe brick with a plaster finish on the interior and exterior surface. The cistern collects water from the roof catchment area and is slowly drained by gravity through a biological filter system of sand and gravel to remove bacteria and small particles. The water works its way into the storage compartment for consumption. Rainwater harvesting calcs determined that the water usage could be reduced by 25% because the cistern could provide 265 litres of treated water (daily).



16.3 Water Management Diagram  
Mid term phase - rainwater treatment and waterless toilet




16.1 Mid Term Floor Plan




16.2 East Perspective  
Rainwater treatment and cistern

Changing to a waterless toilet has reduced water usage 364 litres per day for a family of four because of the water saved from toilet flushing. Thermophilic composting decomposes organic matter until it is broken-down into nutrient rich soil. The existing water storage tower was enclosed with adobe brick to create a compost storage bin. Oxygen, high temperatures, and a 12 month compost cycle destroys all pathogenic bacteria. Each compost bin was sized to hold 34 cubic feet of compost. Once the compost bin is full, the compost is transported to the multi-step compost bin. The compost will spend 4 months in each bin until the 12 month cycle is complete. The compost is then ready to be used as fertiliser.



17.1 Section at Compost Toilet  
Water tower and compost storage



**Results**

**rainwater harvesting:**  
25% total reduced usage of treated water

17.4 Water Usage  
Domestic water consumption

**compost toilet:**  
25% total reduced usage and provides fertiliser



17.2 SouthEast Perspective  
Backyard of house



17.3 Multi-Step Compost Bin  
12 month cycle composting

# Water Management - Long Term Phase

Observing the Troncones daily water usage data, cost data, and the mismanagement of water resources reinforced the importance to construct a long term, low tech solution that would maximize water harvesting with new roof catchment areas. The new roof addition at the expanded exterior kitchen counter and the roof of the compost bin collected untreated rainwater in barrels for irrigation use. The rest of the roof catchment areas drained rainwater into the cistern for domestic water use. The treated water is then pumped up into the gravity fed storage tank using a hydraulic ram pump. 638 sf of new roof catchment area and 1,292 sf of existing roof catchment area reduced water usage by 37% because of rainwater harvesting. Water usage was reduced by 25% with the use of a waterless toilet. An average of 394 litres of rainwater was available daily. The long term conditions provided 62% less water usage.

### Troncones daily water usage:

kitchen faucet 9.5 litres per min.  
 (4 minute average) = 38 litres  
 bathroom faucet 9.5 litres per min.  
 (2 minute average) = 19 litres  
 showerhead 12 litres per min.  
 (7 minute average) = 84 litres  
 toilets 13 litres per flush  
 (7 flushes per person) = 91 litres  
 cooking and drinking water  
 (consumed per person) = 5 litres  
 irrigation (flora) = 125 litres  
**362 litres total per person**

### water cost for trucked water:

.045 pesos per litre, water tank  
 holds 10 cubic meters (450 pesos)  
 .65 pesos per litre of bottled  
 potable water, 20 litres per bottle  
 (13 pesos)

19.32 pesos per person/day

18.4 Daily Water Usage Statistics  
 Troncones average usage per person

### rainwater harvesting calcs:

$g/cd \times population = gpd$   
 $70.37 \times 4 = 281.48$  gallons per day  
 $gpd \times 365 \text{ days} = gal/year$   
 $281.48 \times 365 = 102,740.20$  gallons per year  
 annual precipitation = 59.35  
 design precipitation = 39.53  
 catchment area (existing & addition) = 1,930 sf  
 roof catchment supplies 37% of total usage  
 38,014 gallons supplied by roof yearly

### 37% total reduced usage

18.3 Rainwater Harvesting Calcs  
 New and existing catchment area



18.1 Long Term Floor Plan




18.2 Water Pump  
 Hydraulic ram pump


●● hydraulic ram pump uses water pressure to move water to gravity fed storage tank

Water cost was reduced to \$7.34 pesos (.73 cents) per person per day and \$2,680 pesos (\$268.00 dollars) per person per year. \$4,365 pesos (\$435.50 dollars) equals 62% savings in water cost per person per year.

Cost savings from reduced water usage and indigenous material use will help provide extra money to maintain and improve the low tech ecological building solutions what were applied to this existing house.



19.1 Rainwater Collection Diagram  
New and existing roof catchment area



19.2 Perspective at Rainwater Harvesting  
New and existing roof catchment area

**Results**

**rainwater collection:**

37% total reduced usage

**compost toilet:**

25% total reduced usage

**total reduced usage:**

62% less water usage

19.3 Rainwater Collection  
Reduced usage

**water cost reduced:**

Cost is 7.34 pesos per person/day (.73 cents)

\$2,680 pesos (\$268.00) per person per year

\$4,365 pesos (\$435.50) saved per person/year

62% less cost

## Conclusion

---

The intent of this thesis was to design an ecologically sustainable housing prototype by phasing short term, mid term and long term solutions to an existing condition. These terms are meant to be a sequenced implementation and progression towards a long term goal. An existing dwelling in the Village of Troncones, Mexico was chosen to phase a series of low tech sustainable solutions for thermal comfort and water management. The dwelling was chosen because of a number of issues. It seemed to neglect some of the traditional design vernacular from the region because it did not use indigenous materials. The interior of the house had hot and humid segmented spaces with no ventilation or solar controls. The cost of water was very expensive because there was no infrastructure for water or sewage and the opportunity for collection of rainwater for reuse was ignored.

Implementing design solutions for all social classes will normalize and advance the technologies. Phasing existing sustainable technologies with the intent of learning more about the technology through experimentation, refinement, and an open dialogue with local indigenous people (who provide the experience of generations) hopefully will help to improve the technology. Evaluating the climatic data for the wind, sun, and rain, talking with the local villagers about water usage, water cost and material usage, and my personal experience of living in the existing conditions reinforced the direction of this thesis. It also has given me the aspiration to personally apply some of the proposed technologies to an existing housing condition in Troncones. Working on this thesis makes one realize how easy it is to waste water when it is readily available and it is not in ones mind-set to conserve as one goes about daily routines. The results that were learned from this thesis have made me think about the possibility of water treatment and reuse at the community scale and the infrastructure that would be necessary to service the entire village of Troncones.

This thesis has taught me to narrow my focus on a few specific topics and to provide the necessary evidence to clearly demonstrate a process that reveals results. This experience seems to bring to light a paradigm shift in architecture towards eco-design and a new awareness for all the Earth's inhabitants.

## Endnotes

---

- 1 Low tech: technologically simple sustainable design strategies.
- 2 Existing housing condition: traditional design vernacular methods not involving sustainability.
- 3 BaSiC Initiative: University of Texas design/build program that teaches how to develop a sustainable housing prototype for community members and students. The BaSiC Initiative housing prototype is based on affordable, adaptable, and sustainable building techniques for housing communities in developing countries. See more about BaSiC Initiative at <http://www.basicinitiative.org>.
- 4 Hassan Fathy: in his book, *Natural Energy and Vernacular Architecture*, Fathy focuses on the use of natural energy to provide passive cooling.
- 5 Practical Action: was founded as ITDG (the intermediate Technology Development Group) by economist Dr. EF Schumacherto. Their goal is to help poor communities deal with the challenges of new technologies. See more about Practical Action at <http://www.practicalaction.org>.
- 6 Windflow studies: silica flour was blown with a hair dryer through a modeled replica of the house to simulate wind patterns at 265° west to 230° southwest.
- 7 Sun path studies: 3d computer renderings modeled sun conditions on the house during winter and summer solstice between the heating period of 10:00 am - 4:00 pm.
- 8 Thermal lag: a measurement of time that it takes solar heat to pass through a material.
- 9 Global Historical Climatology Network: monitors climate patterns, see <http://www.ncdc.noaa.gov>
- 10 C.W. Thornthwaite water balance data: the book, *Average Climatic Water Balance Data of the Continents*, analyzes average water cycles of the state of Guerrero, Mexico.

## Annotated Bibliography

---

**Fathy, Hassan.** *Natural Energy and Vernacular Architecture : principles and examples with reference to hot arid climates.* **Chicago, Illinois: University of Chicago Press, c 1986.**

Hassan Fathy worked to re-establish the use of mud brick as an appropriate technology for housing for the poor. Fathy believed that countless experiments and the experience of generations of builders would aid in producing a successful solution to architecture. He focused on the use of natural energy to provide passive cooling for hot climates.

**Kennedy, Joseph F.** *Building Without Borders: Sustainable Construction for the Global Village.* **Gabriola Island, British Columbia: New Society Publishers, c 2004.**

Design/build methods for developing countries is the general focus of this book. The book provides discussion about shelter and sustainable development using low tech building technologies. The primary material discussions deal with using local resources to develop thermal mass systems with adobe brick. Practical Action (ITDG) addresses problems with housing, resources, and environmental restoration.

**Van Der Ryn, Sim.** *Ecological Design.* **Stuart Cowan. Washington, D.C.: Island Press, c 1996.**

Ecological Design discusses the much needed response to the environmental crisis by making connections between nature, culture, values, power relationships, and technology. It stresses the importance of creating a designed environment that reveals the interconnection of technology with the natural world. The book focuses on ecological design that minimizes environmentally destructive impacts by integrating itself with living processes.

**Palleroni, Sergio.** "Basic Initiative", [electronic bulletin board] available from **[www.basicinitiative.org](http://www.basicinitiative.org)**

Basic Initiative teaches design/build sustainable architecture at the University of Texas at Austin. Students work with community members in developing countries to provide a sustainable housing prototype that can be repeated in future projects. The design/build process focuses on the use of locally available and sustainable materials.

## Bibliography

---

1. Ahmed, Shafiul. "Rainwater Harvesting." Practical Action. Available from <http://practicalaction.org/water-and-sanitation/>. Internet; accessed 23, November 2007.
2. Benjamin, Stein, John S. Reynolds, Walter T. Grondzik and Alison G. Kwok. **Mechanical and Electrical Equipment for Buildings**. New Jersey: John Wiley & Sons, 2006.
3. Blanca, Jimenez. "Irrigation in Developing Countries Using Wastewater." **International Review for Environmental Strategies**. Vol. 6, No. 2, 2006, pp. 229-250.
4. Enger, Eldon D., and Bradley F. Smith. **Environmental Science: A Study of Interrelationships**. New York: McGraw-Hill, 2000.
5. Jenkins, Joseph. **The Humanure Handbook: A Guide to Composting Human Manure**. White River Junction, VT: Chelsea Green Publishing, 2005.
6. Laboratory of Climatology (C.W. Thornthwaite Associates). **Average Climatic Water Balance Data of the Continents**. Centerton, New Jersey: The Laboratory, 1964.
7. Yeang, Ken. **Ecodesign: A Manual for Ecological Design**. Great Britain: Wiley-Academy, 2006.

# Appendix: Thesis Presentation Boards

## Phasing Sustainability

### low tech sustainable housing prototype in developing countries


**low tech:** the use of low cost indigenous materials and methods to easily achieve a sustainable design

**sustainable:** biointegration of artificial systems to natural systems

**housing prototype:** a successful, sustainable solution that can be used as a repeatable template

**developing country:** relatively low standard of living, inadequate infrastructure, non-sustaining economic growth and social conditions

Afghanistan Albania Algeria Angola Antigua Argentina Armenia Azerbaijan Bangladesh Barbados Barbuda Belarus Belize Bhutan Bolivia Bosnia-Herzegovina Botswana Brazil Bulgaria Burkina Faso Burundi Cambodia Cameroon Central African Republic Chad Chile Colombia Comoros Congo Congo (DRC) Congo (RDC) Costa Rica Croatia Cuba Czech Rep. Democratic Republic of Congo Djibouti Dominica Dominican Republic East Timor Ecuador Egypt El Salvador Equatorial Guinea Eritrea Estonia Ethiopia Fiji Islands Gabon Gambia Ghana Grenada Guatemala Guinea-Bissau Guyana Haiti Honduras Hungary India Indonesia Iran Iraq Ivory Coast Jamaica Jordan Kazakhstan Kenya Kiribati Kyrgyzstan Laos Latvia Lebanon Lesotho Liberia Libya Lithuania Madagascar Malawi Malaysia Maldives Mali Marshall Islands Mauritania Mauritius Mexico Micronesia, Fed. Sts. Moldova Mongolia Morocco Mozambique Myanmar Namibia Nepal Nicaragua Niger Nigeria North Korea Oman Pakistan Palau Panama Papua New Guinea Paraguay People's Republic of Benin People's Republic of China People's Republic of Congo Peru Philippines Poland Republic of Cape Verde Republic of Georgia Republic of Macedonia Republic of Yemen Romania Russia Rwanda Saint Kitts Saint Vincent Saint Lucia Sao Tome & Principe Saudi Arabia Senegal Serbia Slovakia Rep. South Africa Solomon Islands Somalia Sri Lanka Sudan Suriname Swaziland Syria Tajikistan Tanzania Thailand Togo Tonga Trinidad Tobago Tunisia Turkey Turkmenistan Uganda Ukraine Uruguay Uzbekistan Vanuatu Venezuela Vietnam West-Samoa Zambia Zimbabwe



The Village of Troncones is located in the state of Guerrero, Mexico on the Pacific coast. 920 permanent residents work in three primary job types within this beach community, which caters to vacationers on beach front rental properties and vacation homes. Service workers do the maintenance and hospitality for the beachfront properties. General laborers are unskilled workers, who do a variety of jobs where ever there is opportunity to make money. Construction workers are skilled in a number of various trades and are in high demand because of the fast development of this beach community. Lack of water management and poor dwelling design relating to thermal comfort has led to the interest of this thesis.



phasing sustainability intro

prevailing winds range on average from 265° West to 230° Southwest

poor thermal comfort in a hot climate

16.5 sf of openings for ventilation on west wall is inadequate

proposed: adding cross-ventilation

calculated sizing required for venting:

15.5k CFM of air flow was needed to be added for ventilation

### existing conditions

average wind direction

average daily wind speed

poor thermal comfort in a hot climate

## 1. phasing cross-ventilation

west perspective

east perspective

## 2. phasing flora for shading

shading for habitation

filtration

re-charge zone

Thermal Comfort

cut opening for ventilation

ridge vent detail

section at venting

interior at venting

air vent detail

airflow diagram

west perspective

east perspective

sun path studies

cross-ventilation:

flora for shading:


**existing conditions**



interior kitchen and dining



poor natural lighting



existing structural system



hot segmented spaces



sun path studies  
winter and summer solstices  
interior heating period 10am-4pm

**1. phasing removal of walls**  
med term proposal: open floor plate  
opening the exterior south wall and the wall between the living space and the kitchen allow the southwest winds to flow deep into dwelling



proposed window at section



east perspective



west perspective



longitudinal section



extending interior

**wall removal:**  
280 sf of wall was removed at kitchen to improve interior airflow >37.3 Btu/h sf (>30 Btu required)

**sliding shutter:**  
24 sf at windows controls airflow/shade


**floor plan**  
scale: 1/8" = 1'-0"  
mid-term

**exterior habitation**

**2. phasing sliding shutter**  
proposal: sliding shutter indigenous palm wood and leaflets used slides shut to control sun and wind



sliding shutter on wood track



view through solar controls at west wall



sliding door solar controls at bedroom



solar controls at west wall

**phasing sustainability** **mid term**

**existing conditions**



inadequate Thermal Lag:  
5.5 hours  
Heat Dry Bangor-20°F  
Lowest Dry Bangor-20°F-egg  
lowest mass temperature is 1/4 of mean daily range = lowest dry bulb



sun path studies  
winter and summer solstices  
interior heating period 10am-4pm

**1. phasing exterior living spaces**  
long term proposal: open floor plate  
exterior dining and kitchen space allows the winds to flow through entire dwelling



east perspective



west perspective


**2. phasing indigenous materials**  
adobe brick  
Troncones soil composition  
Cambisol - sandy loam  
Metamorphic - exposed subsurface rocks by soil erosion  
desirable soils for brick-making:  
soils classified as loamy sands, sandy loams or sandy clay loams contain sand, clay, and silt ideal for making adobe brick

**procedure**

mix	form	cure

4.9 pesos per adobe brick (labor & mat)  
7.1 pesos per fired clay brick (labor & mat)  
**31% cost savings**

indigenous roof (repair and addition)  
More Concrete  
Roofing tiles (MCR):  
local resource reflects UV rays  
Roofing Weight (kg/m<sup>2</sup>) 45-50  
MCR tiles 21-30



night ventilation of thermal mass

post & beam concrete rigid frame w/ adobe clay brick infill & stucco finish  
thermal mass:  
1.6 U-value for a 12" adobe wall = 12-hour thermal lag heating period: 10am-8pm (above 80°F)  
heat released after night time drop in temp. sensible heat gain = 1,906 Btu/h  
field stone & grout foundation

**interior kitchen and dining**


**exterior living spaces:**  
exceeds 45 Btu/h sf required for a 2 bedroom dwelling  
**indigenous materials:**  
adobe brick: 31% cost savings  
MCR tiles: lightweight & reflects UV rays  
**thermal mass:**  
1.6 U-value = 10 hour thermal lag  
sensible heat gain = 1,906 Btu/h

**phasing sustainability** **long term**



### existing conditions

Troncones daily water usage:  
**362 litres per person**  
 water cost for trucked water:  
**19.32 pesos per day**  
**7,044.50 pesos per person per year**  
**water costs 11.3% of a person's average income**



### 1. phasing rainwater collection



east perspective

**rainwater harvesting calcs:**  
 g/cd x population = gpd  
 70.37x4 = 281.48 gallons per day  
 gpd x 365 days = gal/year  
 281.48x365 = 102,740.20 gallons per year  
 annual precipitation = 59.53  
 catchment area (existing) = 1,292 sf  
 of roof catchment supplies 25% of total usage  
 25,685 gallons supplied by roof yearly  
 25% total reduced usage

perspective at rainwater collection


**existing conditions**  
 family of four uses 102,740.20 gallons per year




**rainwater collection:**  
 25% total reduced usage  
 53% of irrigation supplied by untreated rainwater

**untreated rainwater for irrigation:**  
 catchment area (existing) = 1,292 sf  
 of roof catchment supplies 25% of total usage  
 53% of irrigation supplied by untreated rainwater

floor plan scale: 1/8" = 1'-0" short-term



rain water collection diagram



## phasing sustainability short term

water management



### existing conditions




potable water used for toilet

### 1. phasing rainwater harvesting



east perspective




**rainwater cistern:**  
 reuse for non-potable use and irrigation



east perspective

### 2. phasing waterless toilet

floor plan scale: 1/8" = 1'-0" mid-term



water management diagram

#### rainwater harvesting calcs:

g/cd x population = gpd  
 70.37x4 = 281.48 gallons per day  
 gpd x 365 days = gal/year  
 281.48x365 = 102,740.20 gallons per year  
 annual precipitation = 59.53  
 design precipitation = 39.53  
 catchment area (existing) = 1,292 sf  
 of roof catchment supplies 25% of total usage  
 25,685 gallons supplied by roof yearly  
 25% total reduced usage



existing dwelling uses 1,364 litres of water per day flushing toilets

compost toilet uses 70 litres of water per day


265 litres of water per day is available for treated water use

1060 litres of water per day is used

proposed savings



compost toilet



section at compost toilet scale: 1/4" = 1'-0"



12 month cycle compost bin

**rainwater harvesting:**  
 25% total reduced usage of treated water  
**compost toilet:**  
 25% total reduced usage and provides fertiliser

## phasing sustainability mid-term

water management



floor plan  
scale: 1/8" = 1'-0"  
long-term

## existing conditions



water truck route



**Trompsburg daily water usage:**  
 kitchen faucet 9.5 litres per min.  
 (4 minute average) = 38 litres  
 bathroom faucet 9.5 litres per min.  
 (2 minute average) = 19 litres  
 showerhead 12 litres per min.  
 (7 minute average) = 84 litres  
 toilets 13 litres per flush  
 (7 flushes per person) = 91 litres  
 cooking and drinking water  
 (consumed per person) = 5 litres  
 irrigation (flora) = 125 litres  
**362 litres total per person**  
**water cost for trucked water:**  
 0.65 pesos per litre, water tank  
 holds 10 cubic meters (450 pesos)  
 60 pesos per litre of bottled  
 potable water, 20 litres per bottle  
 (12 pesos)  
**19.32 pesos per person/day**

## 1. phasing additional water harvest



rain water collection diagram




638 sf of roof catchment area added with dining/living space and bedroom

1000 litres = 1 cubic meter  
3.78 litres = 1 US gallon

### rainwater harvesting calcs:

g/cd x population = gpd  
 70.37 x 4 = 281.48 gallons per day  
 gpd x 365 days = gal/year  
 281.48 x 365 = 102,741.30 gallons per year  
 annual precipitation = 59.33  
 catchment area (existing & addition) = 1,930 sf  
 roof catchment supplied 37% of total usage  
 38,214 gallons supplied by roof yearly

**37% total reduced usage**



**rainwater collection:**  
 37% total reduced usage  
**compost toilet:**  
 25% total reduced usage  
**total reduced usage:**  
 62% less water usage  
**water cost reduced:**  
 7.24 pesos per person/day (73 cents)  
 2,680 pesos (\$268.00) per person per year  
 4,265 pesos (\$426.50) saved per person/year

long term

phasing sustainability

water management