

*Project funding provided by customers of Xcel Energy
through a grant from the Renewable Development Fund.*

Optimizing Energy Production and Use for a

NET-ZERO ENERGY DAIRY

Eric Buchanan MFEC 2017



NET-ZERO: What is it?

How do we get there?

STEP 4: Renewable Energy

STEP 3: Convert Thermal Loads


STEP 2: Energy Efficiency

STEP 1: Understand Energy Usage



STEP 1: UNDERSTAND ENERGY USAGE


❖ Milking cows is energy and water intensive



STEP 1: UNDERSTAND ENERGY USAGE


❖ Where is energy used? The 4 C's:

Wisconsin Dairy Energy Use* (2005)



*Wisc. Dept. of Ag,
Trade & Consumer
Protection, 2006,
Dairy Farm Energy
Mgmt Handbook


30 Farms from HCCC Dairy Energy Use* (2015)



*Dairy Energy Efficiency: Dairy
Cooperative Partnerships for
Improved Energy Efficiency
Program Adoption, May 29, 2015
by The Minnesota Project, Inc.



WCROC Dairy Parlor Total Energy Use

Gas & Electric \approx 2650 MJ/day (740 kWh/day)




STEP 1: UNDERSTAND ENERGY USAGE

- ❖ Current project focuses on the WCROC Milking Parlor
- ❖ Extensive energy monitoring began in late 2013
 - ❖ 20 individual electric load sensors, 11 water flow & temp sensors



STEP 1: UNDERSTAND ENERGY USAGE

❖ Looking at energy per unit of production



WCROC Milking Parlor Energy Usage				
Energy Usage	2013 - 2016			
	Annual Ave.	Ave./cow	Ave./cwt milk	\$/cwt milk
Natural Gas (therm)	4,767	23.6	0.2	\$ 0.12
Electricity (kWh)	111,708	553.0	3.9	\$ 0.39
Total Energy (MJ)	936,314	4635	32.9	\$ 0.52
Total Water (gal)	478,362	2368	16.8	--

Energy costs per cwt of milk are not large, but total annual energy costs are about \$14,700




STEP 1: UNDERSTAND ENERGY USAGE

❖ A deeper dive: parlor total energy usage (natural gas & electricity)

2015 - 16 Dairy Parlor Total Energy Usage

Gas & Electric \approx 2650 MJ/day (740 kWh/day)



70% more total energy is consumed in the winter compared to summer due to parlor heating.

Parlor heating is the largest single load followed by water heating.



UNIVERSITY OF MINNESOTA

Driven to DiscoverSM


STEP 2: ENERGY EFFICIENCY

- ❖ Reducing energy usage is an important step that will reduce the size of any needed renewable energy (RE) system
- ❖ There is no unit of energy cheaper than one you don't use!
- ❖ Energy efficiency upgrades often pay back in under 10 years
 - ❖ MN project HCCC average payback estimates:
 - ❖ LED lights – 3.3 yrs, Electric water heaters – 6.2 yrs
 - ❖ VFD's – 6 to 14 yrs, RHR – 7.8 yrs, Plate Cooler – 9.5 yrs
- ❖ A smaller RE system enhances payback times




STEP 2: ENERGY EFFICIENCY

❖ Lessons learned from WCROC energy monitoring



Vacuum motor = 10 hp (7.5 kW), Cost = \$3,400
 Savings = 38 kWh/day (\$3.80/day)
 Pay back = 2.5 years
 VFD failed after 3 years and was replaced
 Cost = \$5600, Pay Back in 4 years



Scroll comp.= 5 hp (3.7 kW), Cost = \$3,080
 Savings = 8898 kWh/yr (\$890/yr)
 Pay back = 3.5 years



UNIVERSITY OF MINNESOTA
 Driven to DiscoverSM

STEP 3: THERMAL LOAD CONVERSION

- ❖ Only required if a Net-Zero operation is desired
 - ❖ It is difficult to replace burned fuels with RE
 - ❖ In MN, solar thermal systems can not replace 100% of thermal loads
- ❖ Electric appliances are typically more efficient than their gas fueled counterparts (95% versus 65%)
 - ❖ Efficiency alone results in large energy savings
 - ❖ But may NOT lead to cost savings if fuel prices are low



STEP3: THERMAL LOAD CONVERSION


WCROC dairy energy optimization goals

1. **Collect thermal energy from milk as a resource**
Stored in large, well insulated water tank
2. **Use stored heat to preheat cleaning water**
Including pressure water
3. **Replace gas water heater & PW with electric models**
Eventually do the same for the furnace
4. **Add solar thermal energy**

STEP3: THERMAL LOAD CONVERSION

Energy optimized milking process – 4 C's

Collection
Cooling
Cleaning
Comfort




UNIVERSITY OF MINNESOTA

Driven to DiscoverSM

STEP3: THERMAL LOAD CONVERSION

Energy optimized milking process



STEP3: THERMAL LOAD CONVERSION

- ❖ WCROC lessons learned:
 - ❖ Tankless water heaters can supply dairy hot water loads, but only if well water is pre-heated
 - ❖ Storage tank size must be sufficient to cool milk
 - ❖ Manure lagoon or fan coil unit could be a good thermal buffer
 - ❖ Heat pump controls need to be customized to deal with fluctuating milk flow
 - ❖ Solar thermal heating is probably not needed if milk heat is fully harvested



STEP 4: RENEWABLE ENERGY SYSTEMS

- ❖ After energy consuming processes have been optimized and thermal loads have been converted to electricity, a RE system can be sized to generate the total annual energy load.
 - ❖ This results in a Net-Zero operation
- ❖ RE systems generally have high up front costs and longer pay back times than efficiency upgrades
 - ❖ Depends on incentives (FTC, MiM, REAP grant, etc.)
 - ❖ Solar PV and small scale wind (<100 kW) are probably the most economical options and certainly the simplest



STEP 4: RENEWABLE ENERGY SYSTEMS


- ❖ **How does it work?**
 - ❖ **A grid-tie system is probably best choice for most farms.**
 - ❖ Batteries are expensive and require maintenance
 - ❖ **Net Metering in MN for systems <40 kW**
 - ❖ Full retail credit for unused electricity
 - ❖ Otherwise, avoided cost rate ($\approx 3\text{¢/kWh}$)
 - ❖ A larger system may still be economical
 - ❖ Need to carefully size system and match use to generation so energy is used “behind the meter”



Commercial Finish Barn Solar PV Study

- 65 kW system for “Net Zero”, but 48 kW is optimal
- 48 kW cost = \$134,400 (\$2.80/Watt in 2016)

Potential Solar PV Systems For Finisher 4




Over 25 years

- 7.2¢/kWh (no incentives)
18 year payback
- 5.0¢/kWh (fed tax credit)
13 year payback
- 3.2¢/kWh (FTC & REAP)
8 year payback

STEP 4: RENEWABLE ENERGY SYSTEMS

- **Grid-tie system components:**
 - DC electricity (solar) and wild AC (wind) have a disconnect switch near the installation site
 - Electricity travels to a disconnect inside bldg.
 - Then to power inverters to be converted to AC
 - Then to AC panel
 - On to the utility meters
 - Finally to the utility electric grid



STEP 4: RENEWABLE ENERGY SYSTEMS

- ❖ **WCROC lessons learned:**
 - ❖ **There are interconnection costs (talk to your utility early!)**
 - ❖ \$100 to \$250 application fee, \$200 to \$600 for a 2 way meter
 - ❖ Interconnecting directly to a transformer incurs linemen charges
 - ❖ There may be stand-by demand charges
 - ❖ **3 phase installations can be problematic**
 - ❖ Mixed phase inverters may not operate properly with a single phase failure
 - ❖ Solution is a phase monitoring relay



Our experience so far

WCROC RENEWABLE ENERGY SYSTEMS

You are
Here

North Turbine
(10kW) &
Solar PV (4kW)

Milking
Parlor

Farrowing
Barn

Finishing
Barn

Solar
Thermal
Panels

Solar PV
(50kW)

South Turbine
(10kW)

Solar PV
(27kW)

Solar PV
(20kW)

GROUND MOUNTED SOLAR

PRO's

- generally simpler
- Allows mounting angle choice
- Probably less expensive
- Easy access for snow removal

Con's

- Takes up valuable space
- In path of debris (mowing/blowing)
- Ground cover/landscaping/fencing



ROOF MOUNTED SOLAR

PRO's

- Out of sight
- Panels are close to the load
- Less chance of damage/vandalism

Con's

- May require engineering study
- May require roof enhancements
- Need to remove panels to re-roof



WCROC RENEWABLE ENERGY SYSTEMS

❖ Solar and snow: 2 days after storm



UNIVERSITY OF MINNESOTA
Driven to DiscoverSM

WCROC RENEWABLE ENERGY SYSTEMS

- ❖ **Small scale wind:**
 - ❖ Small wind industry is not as mature as solar
 - ❖ Pricing, service, warranties, etc. are all less stable than with solar
 - ❖ **Performance is highly dependent on local wind speed & site**
 - ❖ Bottom of rotor should be 30' above anything within 300'
 - ❖ **Good tower height \approx 100' (30 meters). Guyed or tilt-down**
 - ❖ Guyed towers are less expensive, but take up more space
 - ❖ Guy radius is $\frac{1}{2}$ to $\frac{3}{4}$ of tower height
 - ❖ Tilt-down towers make maintenance easier
 - ❖ **Small turbines can be louder than utility scale turbines**



WCROC RENEWABLE ENERGY SYSTEMS

General guidelines:

- ✓ **Use NABCEP certified contractors**
 - ✓ Find someone who has experience with what you want to do
 - ✓ A good contractor can help you apply for incentives and permits
- ✓ **Talk to the utility company early on**
 - ✓ Understand costs, interconnection requirements, and timeline
 - ✓ Inverters must have UL 1741 listing
- ✓ **Check local and county ordinances for set back req.'s, etc.**



QUESTIONS?

Resources:

- <http://www.cleanenergyresourceteams.org>

CERT's is a great educational site and a portal to almost any RE information

- <https://wcroc.cfans.umn.edu/energy-dairy>

The WCROC site hosts a renewable energy guidebook, dairy energy guidebook & decision tool, as well as information relating to our ag energy projects

- <http://www.dsireusa.org/> The definitive web site for all energy incentives
- <http://pvwatts.nrel.gov/> Free Solar PV prediction tool
- <http://smallwindcertification.org/home/> Independent certification for wind turbines